

Thermoelectric Cooler Performance Specifications


热电模块性能规格书

HP-071060-30X34 W150mm

Hot Side Temperature(°C)热面温度(°C)	25 °C	50 °C
Qmax (Watts)最大制冷量(w)	31	31
Delta Tmax(°C)最大温度差(°C)	68	75
I <sub>max</sub> (Amps)最大输入电流 (A)	6	6
V <sub>max</sub> (Volts)最大输入电压 (V)	8.6	9.1
ModuleResistance(Ohms)电阻值 (Ω)	1.25	1.41





\*\*Tolerances for thermal and electrical parameters ± 10%.

热电参数的公差 ±10%




Performance Curves Th=25 °C (性能曲线 Th=25°C)

Performance Curves Th=50 °C (性能曲线 Th=50°C)



Mechanical Drawing (示意图) :



**Operation Tips:**

操作提示:

- **Max Operating Temperature: 90°C.**  
最大工作温度:90°C
- **Do not exceed I<sub>max</sub> or V<sub>max</sub> when operating module.**  
不超过最大电流或最大电压操作模块
- **Please consult P&N Technology for moisture and corrosion protection options.**  
防潮防腐事项请咨询鹏南科技

**Address:** 5/F Xinfei Building 28<sup>th</sup> Xiangming Road, Torch (xiang'an) Hi-tech Zone, Xiamen Fujian China.

地址: 中国福建省厦门火炬高新区(翔安)产业区翔明路28号新飞大厦5楼

**Sales Tel:** + 86 - 592 - 352 1988

**Fax:** +86-592-352 1989

**Postcode:** 361 011

**Web:** [www.pengnantech.com](http://www.pengnantech.com)